

DH-PFS3110-8P-96

8-Port PoE Switch (Unmanaged)



Features

- > Two-layer industrial PoE switch
- > MAC auto study and aging, MAC address list capacity is 8K
- > Support IEEE802.3af, IEEE802.3at standard
- > Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards
- > Industrial wide temperature design

DH-PFS3110-8P-96

Technical Specifications

Model	DH-PFS3110-8P-96
Ethernet Port	1*1000 Base-X、 1*10/100/1000 Base-T、 8*10/100 Base-T (PoE power supply)
PoE Power Consumption	Each power $\leq 30W$, Total $\leq 96W$
PoE Protocol	IEEE802.3af、IEEE802.3at
Switching Capacity	7.6G
Packet Forwarding Rate	4.17Mpps
Packet Buffer Memory	1Mb
MAC Table Size	8K
Flow Control	Enable by default
Application Humidity	10%—90%
Power	Default DC53V power adapter
Lightning Protection	Common Mode 4KV Differential Mode 2KV
Working Temperature	- 30℃ ~65℃
Weight	540g
Dimension(W×D×H)	150mm×100mm×42mm

Accessories

Model	
PFT3950	1.25G 850nm,500m,LC, Multi-mode
PFT3960	1.25G 1310/1550nm,20km,LC, Single-mode
PFT3970	1.25G 1550/1310nm,20km,LC, Single-mode

Dahua Technology Co., Ltd.

1187 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email:overseas@dahuatech.com

DH-PFS3110-8P-96

www.dahuatech.com

*Design and specifications are subject to change without notice.

© 2012 Dahua Technology Co., Ltd.